

/ Descriptions

SOT-89 PNP Silicon PNP transistor in a SOT-89 Plastic Package.


/ Features

 , 2SD1767
Low $V_{CE(sat)}$, complements the 2SD1767.


/ Applications

Medium power amplifier applications.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter


/ Marking

h_{FE} Classifications Symbol	P	Q	R
h_{FE} Range	82 180	120 270	180 390
Marking	HBDP* _‡	HBDQ* _‡	HBDR* _‡


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-80	V

Colle

/ Electrical Characteristic Curve



/ Marking Instructions



H

BD

P h_{FE}

**

Note:

H: Company Code.


BD: Product Type.

P h_{FE} Classifications Symbol

**:

Lot No. Code, code change with Lot No.

() / K\d g\iXk i\`Gif]`d`]fi @ `l \]f n`Jf d\ `i e^ZGY\$=i\`z



Note:

- | | | | | | |
|---|-------|-----|----|------------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 °C, Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5 °C, Duration:5±0.5sec. |
| 3 | | | 2 | 10 °C/sec. | 3. Cooling Speed: 2~10 °C/sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-89	1,000	7	7,000	8	56,000	7 ×12	180×120×180	385×257×392

/ Notices