

BRCS120P04YBQ
Rev.A Dec.-2022



DATA SHEET

Absolute Maximum Ratings($T_a=25^\circ\text{C}$;)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	-40	V
Drain Current - Continuous	$I_D(T_c=25^\circ\text{C})$	-41	A
Drain Current – Pulsed	I_{DM}	-72	A
Gate-Source Voltage	V_{GS}	≤ 20	V
Power Dissipation	$P_D(T_c=25^\circ\text{C})$	30	W
Single Pulse Avalanche Energy($L=0.5\text{mH}$)	E_{AS}	317.5	mJ
Avalanche Current($L=0.5\text{mH}$)	I_{AS}	-31.5	A
Junction and Storage Temperature Range	T_j, T_{stg}	-55 to 150	-
Thermal resistance, junction - ambient	$t \leq 10\text{s}$	$R_{\theta JA}$	22
	Steady-State		55
Thermal resistance, junction - case	Steady-State	$R_{\theta JC}$	4.2

 Electrical Characteristics($T_a=25^\circ\text{C}$;)




Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$I_D=-250\text{A}, V_{GS}=0\text{V}$	-40	-48		V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-40\text{V}, V_{GS}=0\text{V}$			-1	μA
Gate-Body leakage current	I_{GSS}	$V_{DS}=0\text{V}, V_{GS}=\pm 20\text{V}$			≤ 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\text{A}$	-1	-1.7	-2.5	V
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=-10\text{V}, I_D=-20\text{A}$		11.6	13.5	m Ω
		$V_{GS}=-4.5\text{V}, I_D=-10\text{A}$		15	25	
Diode Forward Voltage	V_{SD}	$I_S=-1\text{A}, V_{GS}=0\text{V}$			-1.2	V
Input Capacitance	C_{iss}	$V_{DS}=-25\text{V}, V_{GS}=0\text{V}, f=1.0\text{MHz}$		4760		pF
Output Capacitance	C_{oss}			2800		
Reverse Transfer Capacitance	C_{rss}			1960		
Gate resistance	R_g	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		17.5		
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=-10\text{V}, V_{DS}=-20\text{V}, I_D=-20\text{A}$		34		nC
Total Gate Charge	$Q_{g(4.5V)}$			17.5		
Gate Source Charge	Q_{gs}			5.8		
Gate Drain Charge	Q_{gd}			9		

Electrical Characteristics(Ta=25℃ ;)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	t _{d(on)}	V _{GS} =-10V V _{DS} =-20V R _L =0.75Ω R _{GEN} =3Ω		11		ns
Turn-On Rise Time	t _r			7.8		
Turn-Off Delay Time	t _{d(off)}			44		
Turn-Off Fall Time	t _f			18		


BRCS120P04YBQ

Electrical Characteristic Curve



BRCS120P04YBQ

, M y f / Marking Instructions



Marking Instructions

BR y , [W A

Q y V ñ —) í D } ö œ

120P04 y ° Z W A

 ÿ D Z W A k š ÿ D Z J

Note:

BR: Company Code

Q: Automobile halogen-free product Code

120P04: Product Type Code

****: Lot No. Code, code change with Lot No

šWD t...•Ž¢ (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KL RU] 9URJKXOTM 6

