

/ Descriptions

TO-252
P-CHANNEL MOSFET in a TO-252 Plastic Package.

/ Features


$V_{DS} (V) = -60V$ $I_D = -14 A$ ($V_{GS} = 20V$)
 $R_{DS(on)1@-10V} 100m$ (Type.83m)
 $R_{DS(on)2@-4.5V} 130m$ (Type.100m)

Qualified to AEC-Q101 Standards for High Reliability, HF Product.


/ Applications

Motor Drive,Power Tools,LED Lighting, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit



/ Pinning






PIN1 G PIN 2 D PIN 3 S PIN 4 D

/ Marking

See Marking Instructions.

Parameter	Symbol	Rating	Unit
-----------	--------	--------	------

/ Electrical Characteristic Curve



Ø □ =) ¢ / Package Dimensions

, M y f / Marking Instructions

BR Q
1C0P06

^a ¢ y

BR y , [W A

Q y V ñ —) í D } ö œ

1C0P06 y ° Z W A

y ÿ D Z W A k š ÿ D Z J

Note:

BR: Company Code


Q: Automobile halogen-free product Code

1C0P06: Product Type Code

*****: Lot No. Code, code change with Lot No

ŠWD t... • Žč (x /) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6

7HPSHUDWUXUH



7LPH VHF

a č y

Note:

- 10• Ä ½ “ † 150 ½ 200 - k ž • 60 ½ 120sec; 1.Preheating:150~200 - , Time:60~120sec.
 20• Q > “ † 255 r5 - k ž • 4 Ò 5 r0.5sec; 2.Peak Temp.:255 r5 - , Duration:5 r0.5sec.
 30• D N ò i Ò 0 , † 2 ½ 10 - /sec. 3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ¯ »] / Resistance to Soldering Heat Test Conditions

“ † y 260 r5 - ž • y 10 r1 sec. Temp.:260±5 Time:10±1 sec

G P á / Packaging SPEC.

2 & x / REEL

Package Type 7>û ~ E	Units ;>û H					Dimension ;>û p . (unit Åmm³)		
	Units/Reel /-	Reels/Inner Box -- /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Reel	Inner Box	Outer Boxç
TO-252	2,500	2	5,000	6	30,000	13 s ×16	360×360×50	380×335×366

ì' x / TUBE

Package Type 7>û ~ E	Units ;>û H					Dimension ;>û p . (unit Åmm³)		
	Units/Tube /•1×	Tubes/Inner Box •1× /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Tube •1×	Inner Box	Outer Boxç
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

„ Ð y f / Notices