

**/ Descriptions**

TO-220F          PNP          Silicon PNP transistor in a TO-220F Plastic Package.

**/ Features**


KTC4511  
Complementary to KTC4511.

**/ Applications**

High Power amplifier application.

**/ Equivalent Circuit**

**/ Pinning**



PIN1 Base          PIN 2 Collector          or          Emitter

**/ h<sub>FE</sub> Classifications & Marking**

h <sub>FE</sub> Classifications Symbol	R	O
h <sub>FE</sub> Ra	55 110 80	160

**/ Absolute Maximum Ratings(Ta=25 )**

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	$V_{CBO}$	-80	V
Collector to Emitter Voltage	$V_{CEO}$	-80	V
Emitter to Base Voltage	$V_{EBO}$	-6.0	V
Collector Current - Continuous	$I_C$	-6.0	A
Base Current	$I_B$	-3.0	A
Collector Power Dissipation	$P_c(T_c=25 )$	30	W
Junction Temperature	$T_j$	150	
Storage Temperature Range	$T_{stg}$	-55 150	

**/ Electrical Characteristics(Ta=25 )**

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Emitter Breakdown Voltage	$V_{CEO}$	$I_C=-25mA$ $I_B=0$	-80			V
Collector Cut-Off Current	$I_{CBO}$	$V_{CB}=-80V$ $I_E=0$			-10	$\mu A$
Emitter Cut-Off Current	$I_{EBO}$	$V_{EB}=-6.0V$ $I_C=0$			-10	$\mu A$
DC Current Gain	$h_{FE}$	$V_{CE}=-4.0V$ $I_C=-2.0A$	55		160	
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=-2.0A$ $I_B=-0.2A$			-0.5	V
Transition Frequency	$f_T$	$V_{CE}=-12V$ $I_C=-0.5A$		20		MHz
Collector output capacitance	$C_{ob}$	$V_{CB}=-10V$ $I_E=0$ $f=1.0MHz$		150		pF

**/ Electrical Characteristic Curve**

