

/ Descriptions



TO-252 NPN Silicon NPN transistor in a TO-252 Plastic Package.

/ Features

， KTA1040D
 Low $V_{CE(sat)}$, complementary to KTA1040D.

/ Applications

General purpose amplifier for surface mount applications.


/ Equivalent Circuit**/ Pinning**

PIN1 Base PIN 2,4 Collector PIN 3 Emitter


/ h_{FE} Classifications & Marking

h_{FE} Classifications Symbol	Y	GR
h_{FE} Range	100 200	150 300

/ Package Dimensions



/ Marking Instructions



BR

C2020D

GR

h_{FE}

Note:


BR: Company Code

C2020D: Product Type.

GR: h_{FE} Classifications Symbol

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

1. Preheating: 25~150 , Time: 60~90sec.
2. Peak Temp.: 245±5 , Duration: 5±0.5sec.
3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.: 260±5 Time: 10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
TO-252	2,500	2	5,000	5	25,000	13 ×16	360×360×50	385×257×392

/ TUBE

Package Type	Units					Dimension (unit mm ³)		
	Units/Tube	Tubes/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Tube	Inner Box	Outer Box
TO-251/252	75	48	3,600	5	18,000	526×20.5×5.25	555×164×50	575×290×180

/ Notices