

LV3045CT

Rev.H Oct.-2018

/ Descriptions

TO-220

Schottky Barrier Diode in a TO-220 Plastic Package.

/ Features

Low forward voltage drop, low power losses, High efficiency operation.


/ Applications

OR-ing

DC-DC

For use in high frequency inverters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.

/ Equivalent Circuit



/ Pinning



PIN1 Anode PIN 2 Cathode PIN 3 Anode

/ h_{FE} Classifications & Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	45	V
Average Rectified Output Current	$I_{F(AV)}$	2 15	A
Non Repetitive Peak Surge Current	I_{FSM}	250	A
Thermal Resistance Junction to Case	R_{Jc}	2.8	/W
Junction and Storage Temperature Range	T_j T_{stg}	-40 +150	



/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Breakdown Reverse Voltage	V_{BR}	$I_R=1mA(Ta=25)$	45			V
Forward Voltage	V_F	$I_F=5A(Ta=25)$		0.38	0.45	V
		$I_F=15A(Ta=25)$		0.48	0.55	V
		$I_F=5A(Ta=125)$		0.28	0.35	V
		$I_F=15A(Ta=125)$		0.45	0.50	V
Instantaneous Reverse Current	I_R Note 1	$V_R=45V(Ta=25)$			200	μA
		$V_R=45V(Ta=125)$		40	100	mA


/Notes

1. /Short duration pulse test used to minimize self-heating effect.
2. / Unless otherwise noted, values for the parameters of a single chip


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



BR

LV3045

CT:

Note:

BR: Company Code

LV3045 Product Type.

CT: Internal Structure

****: Lot No. Code, code change with Lot No.

