


RS2AB~RS2MB
Rev.A Sep.-2019

@ <i>f</i> Parameter	... Z Symbol	<i>f</i> , Rating							% <i>y</i> Unit
		RS2AB	RS2BB	RS2DB	RS2GB	RS2JB	RS2KB	RS2MB	
Maximum Repetitive Peak Reverse Voltage	V_{R50}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V

Electrical Characteristic Curve




, My f / Marking Instructions

Marking

Type number	Marking code
RS2AB	RS2A
RS2BB	RS2B
RS2DB	RS2D
RS2GB	RS2G
RS2JB	RS2J
RS2KB	RS2K
RS2LB	RS2L
RS2MB	RS2M

Marking Instructions




^a ϕ y
 89 'y ° ZWA
 **** y ÿD Z AÇ A k † v Å W A k e µ ϕ Å 4 ZWA

Note:

89 'y Product Type Code
 **** y À 0A&— Ø Â 1GrÉ !W ” 0The 1stote:

šWD t... • Žč (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6



^ačy

- 1o• Ä ½ “ † 25 ½150 - k ž • 60 ½90sec;
- 2o• Q › “ † 245 r5 - k ž • 4 Ö 5 r0.5sec;
- 3o•D N ò i Ò 0 , † 2 ½10 - /sec.

Note:

- 1.Preheating:25~150 - , Time:60~90sec.
- 2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.
- 3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p - »] / Resistance to Soldering Heat Test Conditions

“ † y 260 r5 - ž • y 10 r1 sec. Temp.:260 r5 - Time:10 r1 sec

G P á / Packaging SPEC.

2 & x / REEL

Package Type ß m ù	Units g m ô h					Dimension g m d Ê (unit ! mm ³)		
	Units/Reel / í	Reels/Inner Box í /ç	Units/Inner Box /ç	Inner Boxes/Outer Box ç/±	Units/Outer Box /±	Reel	Inner Boxç	Outer Boxž
SMB	3000	5	15000	5	75000	7 s x11	185X180X105	390X385X205

„Đ y f / Notices