

5 é / Descriptions

n μ É x ... v 8 â ' k F g 9 y < d < k 3 g v y ' k 9 3 (/ xož
Surface Mount General Purpose Silicon Rectifiers, Reverse Voltage y 50 to1000V,Forward
Current:5.0A ,SMB package.

α a / Features

ì ø dý / ì k — ` ... ` , (8 U . 9 6 X + ; k n μ É xož —) í D } ož
Glass Passivated Chip Junction, Lead free in comply with EU RoHS 2011/65/EU directives, For
surface mounted applications. Halogen free product.

Đ ÷ / Applications

%² " (
General purpose.

Ã W] Ô . / Equivalent Circuit

• Ů - æ / Pinning

, M V / Marking

• - ~ a ¢ ož See Marking Instructions.

Ō ? d • Ž ¢ / Electrical Characteristic Curve

Ø □ =) ¢ / Package Dimensions

, M y f / Marking Instructions

, M y f / Marking Instructions

9 '

^a ¢ y
 9 ' y ° Z W A
 **** y ÿ D Z AÇ A k † v ã W A k e µ ¢ ã 4 Z W A

Note:

9 ' y Product Type Code
 **** y Lot No. Code kThe 1st means:YM Code kThe last 3 means:little Lot No
 Code

S5AB~S5MB